

WWD320 WCS PWash&8kg

W1 Front-loading washing machine best wash results in no time



- Cleaning cannot be faster QuickPowerWash
- Gentle laundry care thanks to the Miele honeycomb drum
- Ironing made easy thanks to preironing
- Perfect supplement for specific applications – CapDosing
- Economical, powerful and no wear and tear – the ProfiEco Motor



EAN: 4002516249429 / material number: 11358810

Construction type	
Suitable for stacking	•
Side-by-side	•
Slot-in	•
Door hinge	right
Model	
Product brand	W1 White Edition
Front-loader	•
Spinning	
Max. spin speed	1,400
Rinse hold	•
"Without spin" function	•
Design	
Appliance colour	Lotus white
Control panel colour	Lotus white
Door design	Obsidian black with white ring
Rotary selector colour	Lotus White
Control panel version	5° incline
Control type	Rotary selector
Display	DirectSensor yellow, 7 segment
Cleaning performance	
PowerWash	•
CapDosing	•
Gentle laundry care	
Honeycomb drum	<u> </u>
Load in kg	8.0
User convenience	
Delay start up to 24 hours	
Time left display	<u> </u>
AutoClean detergent drawer	•
Efficiency and sustainability	
Energy efficiency class (A - G)	_ <u>A</u>
Weighted energy consumption per 100 operating cycles for the wash cycle in kWh	47
Weighted water consumption per cycle in I	47
Spin efficiency class	
Acoustic airborne noise emission class (spin cycle)	A
Sound emissions during spin cycle in dB(A) re 1 pW	70
Duration of the "ECO 40–60" programme at nominal capacity	219
Low temperature wash "Cold" and "20 °C"	•
Automatic load control	•
Automatic load control	
Foam sensing	•

more information: http://www.miele.co.uk/domestic



WWD320 WCS PWash&8kg

W1 Front-loading washing machine best wash results in no time



Wash programmes	
QuickPowerWash	<u> </u>
Cottons (coloureds)	<u> </u>
Minimum iron	•
Delicates	•
Shirts	•
Woollens (hand-washable)	•
Express 20	•
Proofing	•
Cottons Eco	•
Separate rinse/Starch	•
Drain / Spin	•
ECO 40-60	•
Quality	
Suds container	Stainless Steel
Counterweights made of cast iron	•
Safety	
Water control system	<u> </u>
PIN code lock	
Optical interface	•
Technical data	
Dimensions in mm (width)	596
Dimensions in mm (height)	850
Dimensions in mm (depth)	643
Appliance depth in mm with opened door	1,077.0
Weight in kg	93.00
Total rated load in kW	2,10-2,40
Voltage in V	220-240
Fuse rating in A	13
Length of supply lead in m	2